

SOUNDOWN CORP.
17 LIME STREET, SUITE 1
MARBLEHEAD, MA 01945

TELEPHONE (781) 598-4248 • (781) 631-9611

1-800-359-1036 • FAX (781) 631-9231

Website <http://www.soundown.com>



FOR PEACE AND QUIET

MATERIALS FOR NOISE REDUCTION


EBOFLOOR - SOUND AND HEAT INSULATION FOR VINYL FLOORS



SOUND INSULATION



GREATER WALKING COMFORT



THERMAL INSULATION

Description:

Ebofloor is a resilient underlayment for use beneath vinyl floors. It gives excellent isolation of airborne noise created by impact (Foot-fall) noise, provides a comfortable walking surface, and it also enhances thermal insulation.

Dimensionally stable PVC floor coverings in roll form and carpets are ideal for laying on Ebofloor.

Linoleum may only be laid on Ebofloor, however it cannot be used in conjunction with chair castors, or when there will be heavy permanent concentrated loads.

Instructions For Use:

Ebofloor can be laid loose or bonded to the floor surface using a dispersion adhesive. Un-bonded assembly with a vinyl floor covering should not exceed a surface area of approximately 750 ft².

Product Data:

Base	Polyester Fiber
Coating	High Quality Latex
Sound Insulation	27 dB to DIN 52210
Impact Sound Insulation	56 dB to ISO 717 (BS5821) part 2
Heat Loss Resistance	.060 m/KW
Fire Grade (Swiss)	Combustibility 5 Smoke Developed 3
Toxicity	Non Toxic BAG T No. 614100
Chair Castor loading	Suitable (DIN 68131)
Material Thickness	.16"
Roll Width	6½'
Roll Length	65½'

Guarentee: In the event of damage which can be demonstrably attributed to the inadequate quality of a Soundown product, the company will replace the product but cannot be held responsible for any consequential damage. Soundown can only accept responsibility for the value of the product sold. The data given in the literature represents the current state of knowledge at Soundown and is given solely for guidance.